

INDICATING DISC GAGE

Indicating disc gages are used to measure I.D's or O.D's around shafts and other obstructions such as grooves, stepped areas, boss type obstacles in the shaft area, or any other configuration that prevents the use of a standard snap, bore, or straight frame shallow diameter gage. Indicating disc gages feature the principle of two point measurement and fixed centralizing locators. Disc gages are made for a specific size with adjustment contacts for minimal bore changes.

FEATURES:

- ✓ Two point measurement.
- ✓ Fixed centralizing locators.
- ✓ .025" gaging contact travel.
- ✓ Can be used with digital or dial indicator.
- ✓ Available with perpendicular indicator.
- ✓ Standard 2 point contact or optional 3 point contact.



Dorsey Products -
proudly made in the USA

ID	
PART #	WITHIN DIAMETER RANGE (INCHES)
IDG-ID-25	0 - .25
IDG-ID-50	.25 - .50
IDG-ID-75	0.50 - .75
IDG-ID-100	.75 - 1.00
IDG-ID-125	1.00 - 1.25
IDG-ID-150	1.25 - 1.50
IDG-ID -175	1.50 -1.75
IDG-ID -200	1.75 - 2.00
IDG-ID -225	2.00 - 2.25
IDG-ID-250	2.25 - 2.50
IDG-ID-275	2.50-2.75
IDG-ID-300	2.75 - 3.75
IDG-ID-325	3.00-3.25
IDG-ID-350	3.25-3.50
IDG-ID-375	3.50-3.75
IDG-ID-400	3.75-4.00
IDG-ID-425	4.00-4.25
IDG-ID-450	4.25-4.50

OD	
PART #	WITHIN DIAMETER RANGE (INCHES)
IDG-OD-475	4.50-4.75
IDG-OD-500	4.75-5.00
IDG-OD-525	5.00-5.25
IDG-OD-550	5.25-5.50
IDG-OD-575	5.50-5.75
IDG-OD-600	5.75-6.00
IDG-OD-625	6.00-6.25
IDG-OD-650	6.25-6.50
IDG-OD-675	6.50-6.75
IDG-OD-700	6.75-7.00
IDG-OD-725	7.00-7.25
IDG-OD-750	7.25-7.50
IDG-OD-775	7.50-7.75
IDG-OD-800	7.75-8.00
IDG-OD-825	8.00-8.25
IDG-OD-850	8.25-8.50
IDG-OD-875	8.50-8.75
FIDG-XXX	For fixed (special) model, add F as prefix
IDG3-XXX	For 3 point contact of interrupted diameters